



FAMILY TENT

(Specification Number 227)



Descriptions

- Water proof, Rot proof and UV Resistant.
- Suitable Family of 5 People
- Large Doors And Windows For optimal Ventilation
- 16m² of Main Floor Area Plus 2 vestibules of 3.5 m² each

DIMENSIONS OUTER TENT

Length x Width: 6.6 x 4.0 Meter
 Central Height: 2.20 Meter
 Wall Height: 1.25 Meter

INNER TENT

Length x Width: 3.95 x 3.8 Meter
 Central Height: 2.10 Meter
 Wall Height: 1.15 Meter

MAIN MATERIALS

- Outer Tent Roof: **350 GSM** PolyCotton Canvas (+/-15%) Waterproof, Rot proof and UV Resistant.
- Outer Tent Wall: **200 GSM** PolyCotton Canvas (+/-10%) Waterproof, Rot proof and UV Resistant.
- Inner Tent: **130 GSM** PolyCotton Canvas (+/-10%) Rot, and UV Resistant.
- Inner Partition: **130 GSM** PolyCotton Canvas (+/-10%) Rot, and UV Resistant.
- Ground Sheet: Sewed in Bathtub Ground Sheet Of (PE) Woven Fabric, **180 GSM** (+/-10%).
- Mud-Flap: Made of White HDPE Fabric **180 GSM** (+/-10%),50 cm as Wall & 20cm as Mud Flap.
- Mosquito Netting: Polyester Mesh
- Frame: 31mm, 4m Ridge Pole (1pcs), 25mm, 2.2m Upright Poles (2pcs), 19mm, 1.4m Door Poles (4pcs), 19mm, 1.25 Wall Poles (6pcs), 31mm, 2.2m Center Upright Pole (1pcs)
- Pegs: 6pcs V-pegs 25x25x3mm 35cm, 4pcs Candy cane Pegs 300x10mm, 26pcs Round head pins 230x6mm.



FAMILY TENT



PERFORMANCE AND CHARACTERISTICS

Self Life: Min.3 years
Color: Natural White
Logo: As per request

FEATURES

Chimney: One Chimney Opening, Size 25 cm x 80 cm, On The Vestibule
Doors: 2 Outer Doors (130 x 140 cm), 2 Inner Doors (100 x 175 cm), One Front One Back
Windows: 2 Full Length Windows (360 x 60 cm)
Ventilation: 2 Ventilation, one on each vestibule

PACKING

Packing Unit: 230 x 30 x 30 cm, 55 KG (+/- 3%)
Content: Outer Tent, Inner Tent, Partition, Frame poles, Instruction Manuel, Pegs, Repair Kits and Hammer

Container Loadability

Containers	With Pallet	Without Pallet
20' GP	16 Pallet, 160 Tents	170 Tents
40' GP	34 Pallet, 340 Tents	340 Tents
40' HC	34 Pallet, 340 Tents	440 Tents

**For All Dimensions and weights a tolerance of 3% is applicable. Indicator weight and container loadability are for your information only and may vary according to products specifications.